

AK1304C Tractor

FEATURES

130hp 4WD with front end loader Euro quick hitch FEL 4 in 1 bucket 1500KG Front End Loader SWL

13 Inch dual functional clutch with metal ceramic friction plate

Dedicated hydraulic pump

forced lift and down

Power steering

Flat and clear deck with side placed gear selections

Heavy duty front axle and wheel rim

Steering wheel adjustable

Seat height adjustable

rear operating levers for lift and hydraulic remote Front loader fit shock Absorption system

MAIN DIMENSIONS

Overall Dimensions(LxWxH) 5150x2490x3280mm

Wheel Base 1750/1700-2300mm Wheel Model front 14.9-26 rear 18.4-38

Axle Base 2740mm

SPECIFICATION

Engine YTO 6 cylinder water cooled

Power 130hp

Hydraulic System Two way

Hydraulic lift: forced lift and down

Flow Rate 50L/Min

Clutch 13" double action clutch

Gearbox 16F+8R shuttle shift

PTO 540/1000 rpm

Battery VARTA 12V/120A

Remotes Hydraulic remotes Dual

Cabin heater, air conditioning, video, monitor,

safety light, hammer,fire extinguisher

Standard counter weight Front:N/A Rear 172kg

FRONT END LOADER

Max.dump height 3810mm Max.dump bucket height 2820mm Dump distance 740mm

Dump angle 58

Rated load capacity 1500kg